Beam Splitters

Compact, rugged and highly efficient opto-mechanical unit for splitting fiber-coupled radiation



FEATURES

Fiber-Coupled Beam Splitters

- Configuration $1 \rightarrow 2$ and $2 \rightarrow 2$
- Highly efficient coupling into singlemode or polarization-maintaining fiber cables
- Compact, rugged, transportable and sealed optomechanical units
- Fully fiber-coupled
- Very high long-term stability, efficiency and reproducability

DESCRIPTION

These fiber-coupled Beam Splitters are compact opto-mechanical units that split a fibercoupled source into two output fiber cables with high efficiency.

Fiber Couplers

A fundamental component of a fiber-coupled Beam Splitter is the <u>Laser Beam Coupler</u>, which is the input into the opto-mechanical unit collimating the input radiation and, finally, couples the radiation back into the polarization-maintaining fiber cables. The stability of the total Beam Splitter is determined by the <u>stability</u> of the laser beam coupler.

ORDER OPTIONS

Order Code	Configuration	Splitting Ratio	Available Wavelength	Transmission	Polarization Extinction
<u>48-MCS-</u> 002	1 → 2	50:50	400 - 1700 nm, monochromatic or bandwidth up to 500 nm	≥ 75 % @ 780 nm	≥ 23 dB @ 780 nm
<u>48-MCS-</u> 011	1 → 2	Dichroic	400 - 1700 nm	≥ 70 % @ 780 nm	≥ 23 dB @ 780 nm
<u>48-MCS-</u> 015	1 → 2	Polarizing	400 - 1700 nm, monochromatic or bandwidth up to 500 nm	≥ 70 % @ 780 nm	≥ 23 dB @ 780 nm
<u>48-MCS-</u> 027	2 → 2	50:50	400 - 1700 nm, monochromatic or bandwidth up to 500 nm	≥ 75 % @ 780 nm	≥ 23 dB @ 780 nm
<u>48-MCS-</u> 026	2 → 2	Polarizing	400 - 1700 nm, monochromatic or bandwidth up to 500 nm	≥ 70 % @ 780 nm	≥ 23 dB @ 780 nm

RELATED PRODUCTS

BEAM SPLITTERS

Compact, rugged and highly efficient optomechanical unit for splitting fiber-coupled radiation

FIBER PORT CLUSTER

This is a printout of the page <u>https://sukhamburg.com/products/fiberoptics/multicube/systems/beamsplitter.html</u> from 5/6/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com



LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]

